





1. Introduction:

A. Proud Owner:

. You are now the proud owner of a Bro-Tek Skid Plate. This Skid Plate (MF-GC-M-R-MMM) is made of 1/8" steel diamond plate. It will outlast your original Kubota tractor & be ready for your next one. Please read these instructions before installing the Skid Plate. The Skid Plate has been designed for easy installation & pre-painted with a very durable paint (Dupli-Color/High Perf Graphite Wheel).

B. Feedback:

. We would love any feedback that you could give us (Positive/Negative) in order to improve our product line. Please email us your comments/pictures too: bro-tek@hotmail.com or visit our web site www.bro-tek.com

Safety Precautions: Important Safety 2.

- A. Park on a firm level area.
- B. Stop engine, set brake, remove key and wait for all moving parts to stop before servicing, adjusting or unplugging.
- C. Block up before working beneath unit.

3. Tools/torque/Parts required:

A. Wrenches or socket (1/2 deep socket... U-Bolts.)









Assembly Instructions: Amportant Safety

. 1 Once you have followed the safety precautions & have removed the skid plate from its packaging, please take note of all the parts & follow the assembly instructions



Free up the work place of all disturbance & clutter. Take your time installing it (This can be easily done by one person in 5 to 10 minutes). Have a good look under your tractor, Mower deck will have to be remove to properly install the skid plate.









install U-Bolts(Photo)locate the predrilled hole on the tractor, like the one shown in the photos below.





.4 Line up the skid plate in a manner that it line up with the hole on the frame. Check clearances around the skid plate so that there are no points of contact other than the mounting locations





.5 Reinstall the two nylon nuts & washers on the u-Bolt andtightening only, this leave some play that will make it easier to line up the skid plate.







- Install a 5/16" bolt with it lock washer& washer, into predrill/hole tighten this one down & the nuts on the U-bolt.
- Check everything out for clearances & binding. Recheck nuts & bolts every month. If attachment is installed, check their clearances with the skid plate & the mower deck (put the Mower Deck in the lowest & highest position. The End on the U-Bolt can be cut down.

ightharpoonupImportant Safety If there is a point of contact, do not continue to use tractor

5. Congratulations:

You have successfully installed your Bro-Tek Skid Plate. I hope this was a pleasant experience & that you would recommend this product to all of your tractor friends. The skid plate can remain on the tractor, for all the preventative maintenances & the everyday use.

6. Thank you:

We would like to thank you for supporting us & hope to do future business with you with, our new upcoming line of products.

